













| NO | Descriptions | | | MOQ Pcs) | Remarks |
|--------------------------------------|--------------|---|---|-------------|---------|
| | Model | Picture | Name | | |
| Honeywell X-618 Digital PA/VA System | | | | | |
| 1 | X-DCS2000/EN |  | Digital Integrated System Manager, 8 Zones, Multi-Functional Integration, without PTT microphone | 1 | |
| 2 | HN-PTT |  | Optional Push-to-talk Microphone (Compatible with X-DCS2000/EN or X-NPMR panel) | 1 | |
| 3 | X-DA2250EN |  | High Efficiency Class D Power Amplifier, 2x250W, 100V/70 Output, with 100 - 240 VAC input and 24 VDC backup power Supply | 1 | |
| 4 | X-DA1500EN | | High Efficiency Class D Power Amplifier, 1x500W, 100V/70 Output, with 100 - 240 VAC input and 24 VDC backup power Supply | 1 | |
| 5 | X-DA4125EN | | High Efficiency Class D Power Amplifier, 4x125W, 100V/70 Output, with 100 - 240 VAC input and 24 VDC backup power Supply | 1 | |
| 6 | X-DA2250 |  | High Efficiency Class D Power Amplifier, 2x250W, 100V/70 Output, with 220 VAC UPS input | 1 | |
| 7 | X-DA1500 | | High Efficiency Class D Power Amplifier, 1x500W, 100V/70 Output, with 220 VAC UPS input | 1 | |
| 8 | X-DA4125 | | High Efficiency Class D Power Amplifier, 4x125W, 100V/70 Output, with 220 VAC UPS input | 1 | |
| 9 | X-DA4060 | | High Efficiency Class D Power Amplifier, 4x60W, 100V/70 Output, with 220 VAC UPS input | 1 | |
| 10 | X-NPMI |  | Configurable Network Paging Console, 4.3" Color Touch Screen, Suitable for Desktop Flush Mount | 1 | |
| 11 | X-NPMI-R | | X-NPMI Rack mounted Panel | 1 | |
| 12 | X-SPT900 |  | X-SMART Med to Small Project System Management Software Package (Include 1 sever and 1 client interface) | 1 | |
| 13 | X-SP2000 |  | X-SMART System Resource Platform (Server) | 1 | |
| 14 | X-ST2000 |  | X-SMART Client Interface | 1 | |
| 15 | HN-SDB40 | | Professional TTS Speech Engine (Standard: Male Voice Chinese & English and Female Voice Chinese x 1, plus Female Cantonese or Female English;Other Languages require separate quotation) | 1 | |
| 16 | X-NRI/EN |  | Network Resource Interface, 4 channels network audio source, 32 dry contacts in and 8 try contacts out | 1 | |
| 17 | X-MAP04 |  | Digital Multi-audio Player | 1 | |

Business terms:

Price: This price is basis on FOB Guangzhou for the FCL order,
Or the delivery terms will be EXW or re-quote the CIF price.

Payment terms : by T/T(30% deposite first, 70% before shipments, 100% in advance for order amount less than \$10,000usd).

Delivery time: Usually 30 days for OEM container order after deposite payments.

Guarantee: 1 year.

Certificate: Complying with the ISO9001:2000, CCC, and CE standards.

OEM AND ODM are welcomed !